

TASKalfa 3510i

BLACK & WHITE MULTIFUNCTIONAL SYSTEM





- > Crisp Output Up to 35 Pages Per Minute
- > Color Scan up to 80 ipm; B&W up to 160 ipm
- > Intuitive and Customizable Touch Screen Control Panel
- > Advanced Finishing Options to Promote Efficiency
- > Robust and Scalable Business Applications

- > Statement 11" x 17" Printing from the Paper Trays
- > Standard Gigabit Ethernet
- > Print on up to 140 lb Index Through Multi Purpose Tray
- > Optional Scan Extension Kit for Searchable PDF
- > Apple AirPrint™ Enabled for a Mobile Printing Solution



ONLY FROM KYOCERA

KYOCERA Document Solutions is a global leader in the digital imaging industry, with an award-winning line of document solutions that consistently set the standard for high performance, superior image quality, workflow-supportive applications, ease-of-use and durability. We get to the heart of your critical business challenges, with a personalized, single source approach that helps streamline your entire document workflow to reduce costs, increase workplace productivity and efficiency, and deliver exceptional results you can count on.

HARNESS THE POWER OF YOUR TASKalfa MEP WITH CUSTOMIZED BUSINESS APPLICATIONS



ACCUSENDER: A simple, secure way to send large scanned documents to multiple destinations via e-mail from select KYOCERA MFPs.



KYOCERA CLOUD CONNECT: Easily print from and scan directly to the cloud while on the go from your KYOCERA MFPs.



DMS LINK: Simplify document workflow through digital imaging, distribution, retrieval and long-time archival.



PINPOINT SCAN: Scan from your MFP to your PC with added speed,



SHAREPOINT CONNECTOR: Enhance collaboration utilizing your KYOCERA MFPs and your existing Microsoft SharePoint Server.

BASIC SPECIFICATIONS

Configuration: Black & White Multifunctional System -Print/Scan/Copy/Optional Fax

Pages Per Minute: Letter: 35 ppm; Legal: 17 ppm; Ledger: 17 ppm Warm Up Time: 23 Seconds or Less (Power On)

First Page Out: Copy: 3.6 Seconds or less; Print: 4.2 Seconds or Less Display: 8.5" Color Control Panel

Resolution / Bit Depth: 600 x 600 dpi; 9600 x 600 dpi interpolated / 8 bit depth

Memory / Hard Disk Drive: 2 GB RAM Standard / 160 GB HDD **Duplex: Standard Stackless Duplex Supports Statement to Ledger** (5.5" x 8.5" - 11" x 17"), 16 lb Bond - 90 lb Index (60 - 163gsm)

Standard Output Tray: Statement - 11" x 17"; 250 Sheets Electrical Requirements: 120V, 60Hz, 11.6A; 220-240V, 50Hz, 6.3A

Dimensions / Weight: 23.39" W x 29.06" D x 26.89" H / 147.7 lbs (excluding toner container weight)

Maximum Monthly Duty Cycle: 150,000 Pages Per Month

Standard Paper Sources:

Dual 500 Sheet Trays, 100 Sheet MPT; Auto Selection/Switching **Optional Paper Sources:**

Dual 500 Sheet Trays (PF-791), Dual 1,500 Sheet Trays (PF-810) Paper Capacity:

Standard: 1.100 Sheets: Maximum: 4.100 Sheets

Paper Size: Trays 1, 2 and (PF-791): 5.5" x 8.5" - 11" x 17"; (PF-810): 8.5" x 11"; MPT: 5.5" x 8.5" - 11" x 17" (Multiple Sheets)

Paper Weight:

Travs: 16 lb Bond - 90 lb index (60 - 163gsm): MPT: 12 lb Bond - 140 lb Index (45 -256gsm)

Input Materials:

Bond Paper, Recycled Paper, Transparencies, Cardstock

SECURITY SPECIFICATIONS

Standard: Local Authentication, Network Authentication (IPsec. HTTPS, LDAP over SSL, SNMPv3); Secure Print (IPP over SSL); Scan to e-mail (POP3/SMTP over SSL); Scan to FTP (FTP over SSL); Scan to SMB/PC/USB; SSL

Optional: Data Security Kit (E): Network Data Encryption, HDD Overwrite Mode, HDD Data Encryption

PRINT SPECIFICATIONS

Standard Controller: Freescale OorIO P1022 (Dual Core) / 800MHz

Standard: PRESCRIBE, PCL6 (5e, XL), KPDL3 (PS3), XPS; Optional: UG-34 IBM ProPrinter, Line Printer, LQ-850

Fonts: 136 KPDL3, 93 PCL6, 8 Windows Vista, 1 Bitmap

Windows OS Compatibility: Windows XP/2003/Vista/2008/7/8/ Server 2008 R2/Server 2012

Novell OS Compatibility: Novel NetWare 3.x/4.x/5.x/6.x

Mac OS Compatibility: OS 10.x; AirPrint Enabled

UNIX OS Compatibility: Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX(LPR)

Interfaces: Standard: 10/100/1000BaseTX, Hi-Speed USB 2.0, 4 USB Host Interfaces, 2 Expansion Slots

Optional: 10/100/1000BaseTX (IB-50 for Dual NIC); Optional: IEEE 802.11 b/g/n (IB-51 for Wireless LAN Interface)

Network Print and Supported Protocols: TCP/IP, NetBEUI, FTP, LPR, IPv6, IPsec, SSL, WSD Print

KX Driver, Mini Driver, KX Driver for XPS, XPS Mini Driver, Network Fax Driver, PPD for MAC

Utilities: KYOCERA Net Admin, KYOCERA Net Viewer, PDF Direct Print, Command Center RX

Scan Type: Color and Black & White Scanner

Scan Resolution: 600 dpi, 400 dpi, 300 dpi, 200 dpi, 200 x 100 dpi,

File Formats: Black and White: TIFF, XPS, PDF, PDF/A; Color: TIFF, JPEG, XPS, PDF, PDF/A

PDF Extension: High Compression PDF, Encrypted PDF, Searchable PDF (OCR) Option

Scan Speeds:

DP-770(B): Simplex: 75 ipm BW, 50 ipm Color (300 dpi); Duplex: 45 ipm BW, 34 ipm Color (300 dpi) DP-772: Simplex: 80 ipm BW, 50 ipm Color (300 dpi); Duplex: 160 ipm BW, 80 ipm Color (300 dpi) DP-773: Simplex: 48 ipm BW/Color (300 dpi); Duplex: 15 ipm BW/Color (300 dpi)

Connectivity / Supported Protocols: 10/100/1000BaseTX, TCP/IP Scanning Functions: Scan to Folder (SMB), Scan to e-Mail, Scan to FTP. Scan to FTP over SSL. Scan to USB. WSD Scan, TWAIN Scan

Through DP: Statement to Ledger (5.5" x 8.5" - 11" x 17"); Glass: up to 11" x 17"

Drivers: TWAIN Driver, WIA Driver

COPY SPECIFICATIONS

Image Mode: Text, Photo, Text/Photo, Auto, Manual, Map

Continuous Copy: 1-999/ Auto Reset to 1

Additional Features: Positive/Negative Reverse, Mirror Image, Rotate Copy, Border Erase, Split Copy, Electronic Sort, Margin Shift, Page Number, Form Overlay, XY Zoom, Prevent Bleed Through, Text Stamp, Bates Stamp, Blank Page Skip

Job Management: 1,000 Department Codes, Job Programs, Job Build, Shortcut Keys, Repeat Copy

Magnification / Zoom: Full Size, 4 Reduction, 4 Enlargement Preset Ratios, 25 - 400% in 1% step increments

Document Box: Custom Box, Job Box, Removable Memory Box, Fax Box (with optional Fax System)

DOCUMENT PROCESSOR OPTIONAL DP-770(B). DP-772 OR DP-773

Type / Capacity:

DP-770(B): Reversing Automatic Document Processor / 100 Sheets DP-772: Dual Scan Document Processor / 175 Sheets DP-773: Reversing Automatic Document Processor / 50 Sheets

Acceptable Originals: 5.5" x 8.5" - 11" x 17"

Acceptable Weights (Simplex / Duplex):

DP-770(B): Simplex: 13 lb Bond - 90 lb Index (45 -160gsm): Duplex: 16 lb - 32 lb Bond (50 - 120gsm) **DP-772:** Simplex: 13 lb Bond - 120 lb Index (35 - 220gsm); Duplex: 16 lb Bond - 120 lb Index (50 - 220gsm)

DP-773: Simplex: 13 lb Bond - 90 lb Index (45 - 160gsm); Duplex: 16 lb - 32 lb Bond (50 - 120gsm)

Fax Type: Fax System W(B) / Internet Fax Kit (A) (requires Fax System W(B))

Compatibility / Data Compression: G3 Fax / MMR, MR, MH, JBIG Transmission Speed / Modem Speed: Approximately 3 seconds per page / 33.6 Kbps

Fax Memory: Standard: 12 MB; Maximum: 120 MB

Driver: Network Fax Driver

Fax Functions: Duplex TX/RX, Confidential RX/TX, F-Code RX/TX, Broadcasting, Fax Box, Dual Fax

OPTIONAL 1,000 SHEET FINISHER DF-770(D)

Stack / Staple Capacity: Main Tray: 1,000 Sheets / 50 Sheets (up to 24 lb Bond (90gsm))

Paper Size: 5.5" x 8.5" - 11" x 17"

Paper Weight: 16 lb Bond - 140 lb Index (60 - 256gsm) Edge Staple Position: 3 Positions: Top Left, Bottom Left,

Optional Punch: PH-7A 2 and 3 Hole Punch Unit, Supports 8.5" x 11" - 11" x 17", 13 lb Bond - 93 lb Cover (45 - 256gsm)

OPTIONAL 3,000 SHEET FINISHER DF-791

Stack / Staple Capacity: Main Tray: 3,000 Sheets; Sub Tray(B): 200 Sheets; Sub Tray(C): 50 Sheets / 65 Sheets: 8.5" x 11"; 30 Sheets: 8.5" x 14", 11" x 17"

Paper Size: Main Tray: 8.5" x 11" - 11" x 17"; Sub Tray(B): 5.5" x 8.5" - 11" x 17"

Paper Weight: 16 lb Bond - 140 lb Index (60 - 256gsm) Edge Staple Position: 3 Positions: Top Left, Bottom Left,

Optional Multi-bin Mailbox: MT-730(B): Includes 7 Travs: Supports 16 lb Bond - 90 lb Index (60 - 163gsm) Stack Capacity per bin: 100 Sheets: 5.5" x 8.5", 8.5" x 11"; 50 Sheets: 8.5" x 14", 11" x 17"

Optional Punch: PH-7A 2 and 3 Hole Punch Unit, Supports 8.5" x 11" - 11" x 17"; 13 lb Bond - 93 lb Cover (45 - 256gsm)

ADDITIONAL OPTIONS

AK-740 (Bridge Unit for Finisher), IB-50 Gigabit NIC (Dual NIC), IB-51 Wireless LAN, Card Authentication Kit (B), Cabinet, Card Reader Holder(E), Keyboard Holder (B), Data Security Kit (E), Scan Extension Kit (A) for Searchable PDF/OCR, Optional Fax Memory

Specifications and design are subject to change without notice. For the latest on connectivity visit www.kyoceradocumentsolutions.com/us AccuSender, KYOCERA Cloud Connect, DMS Link and PinPoint Scan are trademarks of the KYOCERA Companies MAC and AirPrint are trademarks of Apple, Inc. Java is a trademark of Oracle Corporation. Other trademarks are the property of their respective owners.

KYOCERA Document Solutions America, Inc. Headquarters: 225 Sand Road, Fairfield, NI 07004-0008, USA ©2013 KYOCERA Document Solutions America, Inc.













